Dahlquist et al.

Date of Patent: [45]

May 10, 1988

[54]	COMPUTER CONTROLLED MULTI-LINK	1352238	5/1974	United Kingdom
LJ	COMMUNICATION SYSTEM			United Kingdom .
[75]	Inventors, Iomes E Deblauist Poletine, Poten	2060316	4/1981	United Kingdom
[/2]	Inventors: James E. Dahlquist, Palatine; Peter			

C. Holtermann, Chicago; Carl P. Rau, Mount Prospect, all of Ill.

Rauland-Borg Corporation, Chicago, [73] Assignee:

[21] Appl. No.: 803,133

Filed: Nov. 27, 1985

[51] Int. Cl.⁴ H04M 3/22; H04Q 1/30; H04Q 3/545; H04Q 3/64 U.S. Cl. 379/247; 379/263;

379/265; 379/269; 379/384

379/165, 247, 284, 290, 217, 263, 265, 269, 383, 384; 370/96

[56] References Cited

U.S. PATENT DOCUMENTS

2,258,650	10/1941	Herrick	379/243
2,261,243	11/1941	Flint	379/262
2,883,472	4/1959	Stehlik	379/159
2,911,477	11/1959	Gohorel et al	379/245
2,966,554	12/1960	Dubois	379/210
3,342,944	9/1967	Barbato et al	379/158
3,350,508	10/1967	Swanson	379/252
3,501,596	3/1970	Bierman	379/208
3,551,601	12/1970	Sloan et al	379/209
3,553,385	1/1971	Morgan et al	379/207
3,584,151	6/1971	Kielar 34	0/825.48
3,660,610	5/1972	Hestad et al	379/203
3,678,208	7/1972	Eddy	379/255
3,697,700	10/1972	Greason, III et al	379/274
3,701,853	10/1972	Duval et al	379/208
3,809,824	5/1974	Dahlquist et al	. 379/48
4,064,377	12/1977	Regan	379/342
4,081,614	3/1978	Dahlquist et al	. 379/49
4,180,860	12/1979	Driscoll et al	
4,289,934	9/1981	Pitroda et al	
4,351,986	9/1982	Fechalos	
4,559,417	12/1985	Komuro et al	
4,570,035	2/1986	Pinede et al	
4,605,825	8/1986	Komuro et al	379/165

FOREIGN PATENT DOCUMENTS

1238103 7/1971 United Kingdom .

OTHER PUBLICATIONS

"ROLMphone (Reg. Trademark) Digital Telephones," ROLM Corp., Santa Clara, California (1983) (12 pages). "ROLMphone (Reg. Trademark) User's Guide," ROLM Corp., Santa Clara, California (1984).

Primary Examiner-Thomas W. Brown Attorney, Agent, or Firm-Leydig, Voit & Mayer

ABSTRACT

A multi-link communication system includes a number of stations and interconnecting audio links under the control of a central computer. Each station is addressable by the computer for connecting selected stations to a selected audio link for establishing audio communication between stations. Each station has at least one corresponding access circuit for establishing an audio connection to a selected or preassigned link, and the connection is maintained by a corresponding memory circuit that is addressable by the computer. A group of output lines from the computer are used as select inputs to an analog multiplexer connecting a bidirectional control line to the selected access circuit for connecting or disconnecting the corresponding station and also for receiving connect or disconnect requests from the corresponding station. In a particular embodiment, the stations include multi-link dial and dialless telephones, single-link dialless telephones, and intercom speakers in an automatic private branch exchange. Latching relays provide audio connections for speakers and dialless single-link phones, and unbalanced analog transmission gates provide audio connections for multi-link phones. The capabilities of each station are encoded as predefined attributes stored in electrically alterable memory, and the attributes of a selected station are user-programmable via the touch-tone dial of an administrative telephone. Standard and priority call-ins from dialless phones and intercom speakers are identified on numeric or graphic displays interconnected to the computer via a shielded wire or shielded balanced pair conveying a pulse-width modulated binary signal.

20 Claims, 25 Drawing Sheets

